

Impeder Bollards 30S & 50S

bristorm



Technical Specifications

	Impeder 30S	Impeder 50S
Height Above Ground	219 mm	324 mm
Foundation Dimensions (mm)	1,000 mm	1,006 mm
Anchorage	400 mm (or cont.)	300 mm (or cont.)
Line Post Spacing	1,400 mm	1,500 mm
Angled Anchor Range	BSI PAS 68: 2010 V/7500(N2)/48/90:0.0/0.0 Minimum tested array - 2 units	IWA 14-1: 2013 V/7200 N2A /80/90:3.0 Minimum tested array - 2 units
Inter Restraint Post Spacing	Steelwork, hot-dip galvanised to BS EN ISO 1461. Alternative aesthetic options are available to suit client requests such as powder coating.	
Tension	Fixed, Shallow High-Security Bollards	

Product Overview

Brought to you by Hill & Smith Barriers, the Bristorm IMPEDER range of fixed, high-security bollards are made up of standard CHS sections, casting concrete or socketed.

The IMPEDER range of bollards has successfully withstood a range of different impact tests certifying the range to be compliant with the BSI PAS 68 & IWA 14 standard at different speeds to suit varying client risk profiles.

Set within either a concrete and rebar foundation or an 'I Beam', these products are supplied with full installation instructions and 'General Arrangement Drawings'.

The steelwork is hot-dip galvanised to BS EN ISO 1461 as standard. Other aesthetic finishes are available on client request such as powder coating to a specified RAL colour.

Bollards are ideal to protect areas which still require access for pedestrians. Unlike road blockers, fences and gates, bollards remain a friendlier and less alarming security measure for areas where security equipment is meant to blend into the surrounding environment. Bollards also aid pedestrian flow through densely populated areas such as fan zones outside stadiums or to protect railway concourses or airport terminal buildings.